

INFOCUS® LP®820 INSTALLATION & INTEGRATION PROJECTOR




VERSATILE CONNECTIVITY... A SMOOTH, GLITCH-PROOF PRESENTATION

The InFocus LP820 is a high-performance projector with meeting room ease and flexibility, all in a low-maintenance package. Want to mount your projector on the ceiling or move it from room to room? Need an upgradeable solution with ultimate reliability? The InFocus LP820 is as easily shared as it is integrated into almost any room.

EASE, INCORPORATED

Imagine. A projector that works the way you do. InFocus ProjectAbility™ makes projecting easier than it's ever been before—from setup, use, options, storage, and management. Exclusively from InFocus.



InFocus®

GET CONNECTED TO OPTIONS

— CONNECTIVITY, FLEXIBILITY.

Ceiling-mount the LP820 or cart it between rooms with its built-in handle for a high-end meeting room solution. With 6 inputs, there's no need for an external switcher for multiple sources. The LP820 is easily networked right out of the box with InFocus ProjectorNet™.

— EASY TO USE, EASY TO MAINTAIN.

With do-it-yourself installation and user-replaceable bayonet lenses that can be changed without tools (just push and twist), you don't need a team of engineers to integrate the LP820 into a room. An intelligent, multilanguage, backlit interactive display guides presenters through setup and use, and color-coded I/O makes connecting easy. Sturdy reliability is built right in with performance you can trust.

— UPWARDLY COMPATIBLE.

Gain complete control from your laptop with InFocus ProjectorManager™, a free application that turns any PC into an advanced projector remote control. Adjust projector settings, switch sources, even access power management controls and presentation collaboration tools. The LP820 is also compatible with the InFocus wireless solution—switch quickly and seamlessly between presenters with InFocus LiteShow®.

FULL-FEATURED. FULL FLEXIBILITY.



Full connectivity and control are yours, in a solutions-enabled design that lets you install the projector in almost any room configuration or move it between rooms.



Connect to multiple computer and video sources.



Mount it on the ceiling, or keep it mobile.



Unobtrusive in the meeting.



Connectivity for maximum collaboration.

— INSTALLATION PERFORMANCE. MEETING ROOM FLEXIBILITY.

With its incredible ease of use and broad compatibility with a variety of sources, the InFocus LP820 creates new versatility in installation projectors. And a perfect image is yours every time—no matter where the projector is in the room—with horizontal and vertical keystone correction. Scroll-and-select menus and an interactive display make it easy for presenters to put on a smooth show, all without the need for studying complicated directions beforehand.

— GET CONNECTED.

Experience superb picture quality, with native XGA resolution, 800:1 contrast ratio, and 3200 lumens. Full-featured with broad connectivity, including 6 inputs (3 video plus 3 PC) and color-coded connections, the LP820 makes connecting to multiple computer and video sources simple for any user.


Controlling multiple installed projectors is easy, thanks to ProjectorNet asset-management software, which allows IT and AV personnel to manage, monitor, and maintain multiple projectors from a single PC, allowing for fast, cost-effective control.

— EASE FOR THE ENTERPRISE.

For presenters, nothing could be easier. The LP820 delivers the most advanced features with none of the hassles. That means one-touch, instant projection. The intelligent 12-language backlit interactive display guides presenters through a smooth presentation that takes ease of use to a new level. The durable ergonomic design lets the presenter handle the projector with confidence and ease. And user-replaceable bayonet lenses can be changed quickly and easily without tools.



INSTALLATION & INTEGRATION PROJECTOR.



PROJECTION DISTANCES LP820 1.8:1 – 2.4:1 Standard Throw Chart

| Distance | | Minimum Image | | | | Maximum Image | | | |
|----------|--------|----------------|--------|-------------|--------|----------------|--------|-------------|--------|
| | | Diagonal Image | | Image Width | | Diagonal Image | | Image Width | |
| 5' | 1.5 m | 2.60' | 0.79 m | 2.08' | 0.64 m | 3.47' | 1.06 m | 2.78' | 0.85 m |
| 10' | 3.0 m | 5.21' | 1.59 m | 4.17' | 1.27 m | 6.94' | 2.12 m | 5.56' | 1.69 m |
| 15' | 4.6 m | 7.81' | 2.38 m | 6.25' | 1.91 m | 10.42' | 3.18 m | 8.33' | 2.54 m |
| 20' | 6.1 m | 10.42' | 3.18 m | 8.33' | 2.54 m | 13.89' | 4.23 m | 11.11' | 3.39 m |
| 25' | 7.6 m | 13.02' | 3.97 m | 10.42' | 3.18 m | 17.36' | 5.29 m | 13.89' | 4.23 m |
| 30' | 9.1 m | 15.63' | 4.76 m | 12.50' | 3.81 m | 20.83' | 6.35 m | 16.67' | 5.08 m |
| 32.8' | 10.0 m | 17.08' | 5.21 m | 13.67' | 4.17 m | 22.78' | 6.94 m | 18.22' | 5.55 m |

PROJECTION DISTANCES LP820 3.0:1 – 5.5:1 Optional Long Throw Chart

| Distance | | Minimum Image | | | | Maximum Image | | | |
|----------|--------|----------------|---------|-------------|---------|----------------|---------|-------------|---------|
| | | Diagonal Image | | Image Width | | Diagonal Image | | Image Width | |
| 16.4' | 5.0 m | 3.73' | 1.14 m | 2.98' | 0.91 m | 6.83' | 2.08 m | 5.47' | 1.67 m |
| 20' | 6.1 m | 4.55' | 1.39 m | 3.64' | 1.11 m | 8.33' | 2.54 m | 6.67' | 2.03 m |
| 25' | 7.6 m | 5.68' | 1.73 m | 4.55' | 1.39 m | 10.42' | 3.18 m | 8.33' | 2.54 m |
| 30' | 9.1 m | 6.82' | 2.08 m | 5.45' | 1.66 m | 12.50' | 3.81 m | 10.00' | 3.05 m |
| 35' | 10.7 m | 7.95' | 2.42 m | 6.36' | 1.94 m | 14.58' | 4.45 m | 11.67' | 3.56 m |
| 40' | 12.2 m | 9.09' | 2.77 m | 7.27' | 2.22 m | 16.67' | 5.08 m | 13.33' | 4.06 m |
| 45' | 13.7 m | 10.23' | 3.12 m | 8.18' | 2.49 m | 18.75' | 5.72 m | 15.00' | 4.57 m |
| 50' | 15.2 m | 11.36' | 3.46 m | 9.09' | 2.77 m | 20.83' | 6.35 m | 16.67' | 5.08 m |
| 75' | 22.9 m | 17.05' | 5.20 m | 13.64' | 4.16 m | 31.25' | 9.53 m | 25.00' | 7.62 m |
| 100' | 30.5 m | 22.73' | 6.93 m | 18.18' | 5.54 m | 41.67' | 12.70 m | 33.33' | 10.16 m |
| 200' | 61.0 m | 45.45' | 13.85 m | 36.36' | 11.08 m | 83.33' | 25.40 m | 66.67' | 20.32 m |

PROJECTION DISTANCES LP820 1.2:1 Optional Short Throw Chart

| Distance | | Image Size | | | |
|----------|-------|----------------|--------|-------------|--------|
| | | Diagonal Image | | Image Width | |
| 3.3' | 1.0 m | 3.44' | 1.05 m | 2.75' | 0.84 m |
| 5' | 1.5 m | 5.21' | 1.59 m | 4.17' | 1.27 m |
| 10' | 3.0 m | 10.42' | 3.18 m | 8.33' | 2.54 m |
| 15' | 4.6 m | 15.63' | 4.76 m | 12.50' | 3.81 m |
| 19.7' | 6.0 m | 20.52' | 6.25 m | 16.42' | 5.00 m |

THE INFOCUS COMMITMENT

Experience for yourself why InFocus Corporation is the worldwide leader in digital projection. Our dedication to quality and customer satisfaction is reflected in service options that will bring you a greater return on your investment. InFocus projectors come with a standard 2-year limited factory warranty, including parts and labor, and a 90-day lamp replacement warranty. Our customer support offers you premium service and convenience, whatever your needs.

For service program details in your region, please visit www.infocus.com/service/service_offerings

OPTIONAL ACCESSORIES

| | |
|----------------|--|
| A650 cm | Screen, Tabletop, 50"/127 cm |
| CA-ATA-017 | ATA-Approved Shipping Case |
| HW-DLXSCRN | Deluxe Insta-Theatre Screen 60"/152 cm |
| HW-INTEGRATOR | Integrator Remote |
| HW-PRESENTER | Presentation Remote |
| HW-RF-POCKTPNT | Mind Path® RF PocketPoint Remote |
| HW-WALLSCR84 | Manual Wall/Ceiling Screen 84"/213 cm Diagonal |
| LENS-020 | Short Throw Lens |
| LENS-021 | Long Throw Lens |
| SP-AV30 | Audio/Video Cable |
| SP-CEIL-005-B | Ceiling Mount |
| SP-DVI-D | Digital Cable, USB + DVI to M1-D |
| SP-LAMP-012 | Replacement Lamp |
| SP-LOCK-B | InFocus Projector Cable Lock |
| SP-LTMT-EXTP | LM+ Extension Arm 26" - 47"/66 cm - 119 cm |
| SP-LTMT-PLT | Ceiling Plate, LiteMount |
| SP-VESA-ADPT | Component to VESA Adapter |
| SP-VGAEXT50-D | VGA 50'/15 m Cable/Line Amp Extension Solution US |
| SP-VGAEXT50-I | VGA 50'/15 m Cable/Line Amp Extension Solution International |

Ships Standard With

- **Conductor+ Full-Featured Remote with Laser Pointer**
- **Color-Coded Cable Straps**
- **VGA Analog Computer Cable**
- **USB Mouse Cable**
- **3.5 mm Computer Audio Cable**
- **RCA Audio/Video Cable**
- **Power Cord**
- **User Manual, Quick Start card and CD**

— TECHNICAL SPECIFICATIONS

| | |
|---|---|
| Native Resolution | • XGA 1024 x 768 |
| Display Technology | • 3 x .99" polysilicon TFT LCD, active-matrix MLA |
| Computer Input Sources | • Computer 1 (M1-D), Computer 2 (VESA), Computer 3 (VESA), audio inputs (stereo 3.5 mm x 2) |
| Video Input Sources | • Video 1 (S-Video), Video 2 (composite RCA), Video 3 (component RCA), audio inputs (stereo RCA x 2) |
| Control Input Sources | • NIC (RJ45), RS232, PS2, USB |
| Output Sources | • Variable stereo audio (RCA), monitor out (VESA) 12V screen trigger |
| Computer Compatibility | • SXGA, XGA, SVGA, VGA, Macintosh™ |
| Video Compatibility | • Full NTSC, PAL, SECAM, EDTV, HDTV (1080i, 1080p, 720p, and 480p RGBHV) |
| Brightness | • 3200 max ANSI lumens |
| Brightness Uniformity | • 85% |
| Contrast Ratio | • 800:1 full on/full off |
| Number of Colors | • 16.7 million |
| H-Synch Range | • 25 - 100 kHz |
| V-Synch Range | • 50 - 85 Hz |
| Dot Clock | • 170 MHz |
| Digital Keystone Correction (horizontal) | • +/- 15°; data/video |
| Digital Keystone Correction (vertical) | • +/- 25°; data/video |
| Projection Lens (standard) | • User-changeable manual zoom lens • Zoom ratio 1.3:1 • Throw ratio 1.8:1 - 2.4:1 (D:W) • Projection distance 5' - 32.8' /1.5 m - 10.0 m • Image offset ratio (%) 100 ± 5% |
| Projection Lens (opt. long throw LENS-021) | • User-changeable manual zoom lens • Zoom ratio 1.8:1 • Throw ratio 3.0:1 - 5.5:1 (D:W) • Projection distance 16.4' and greater (5 m and above) • Image offset ratio (%) 100 ± 5% |
| Projection Lens (opt. short throw LENS-020) | • User-changeable fixed focal length lens • Zoom ratio not applicable • Throw ratio 1.2:1 (D:W) • Projection distance 3.3' - 19.7' /1.0 m - 6.0 m • Image offset ratio (%) 100 ± 5% |
| Aspect Ratio | • 4:3 |
| Image Size (diagonal) | • 40" - 200" /101.6 cm - 508.0 cm |
| Projection Methods | • Front, rear, and ceiling |
| Audio (on-board) | • 2x1-watt stereo |
| Projector Interface | • User LCD interface or menu system |
| Menu Languages | • English, Spanish, French, German, Japanese, Korean, Portuguese, Italian, Norwegian, Russian, Chinese Simplified, Chinese Traditional |
| Projector Control | • IR Remote, keypad, ProjectorManager, RS 232, NIC (RJ45), ProjectorNet |
| Mouse Control | • USB, PS2 |
| Lamp | • 250W UHP / 2000 hours* |
| Dimensions | • 4.3" x 13.1" x 15.6" /11.0 cm x 33.3 cm x 39.7 cm |
| Weight | • 13.1 lbs/6.0 kg |
| Power Consumption | • 350 watts |
| Power Supply | • 100V - 240V at 50 - 60 Hz |
| Operating Temperature | • 10° - 35° C at sea level (0 - 10,000'); 50° - 95° F |
| Audible Noise | • 38 dB (standard mode); 34 dB (whisper mode) |
| Approvals | • FCC A (US/Canada), S-JQA (Japan), PSE (Japan), CCC (China), IRAM (Argentina), GOST (Russia), UL & cUL (US/Canada), TUV GS (Germany), NOM (Mexico), MIC (Korea), C-Tick (Australia) |
| Lamp Warranty | • 90 days or 500 hours, whichever comes first |
| Product Warranty | • 2 years: parts and labor |
| Accessory Warranty | • 1 year |

* Actual lamp life may vary based on the ambient environment. Conditions that may affect lamp life include temperature, altitude, rapidly switching the projector on and off, and switching between standard and low power modes.

† InFocus Corporation reserves the right to alter product offerings and specifications at any time without notice.

Contact InFocus or your dealer today.



www.infocus.com

InFocus Corporate Headquarters:

27700B SW Parkway Avenue • Wilsonville, Oregon 97070-9215, USA
Phone: 503-685-8888 • 1-800-294-6400 • Fax: 503-685-8887

In Europe: InFocus International BV

Strawinskylaan 585 • 1077 XX Amsterdam • The Netherlands
Phone: (31) 20 5792000 • Fax: (31) 20 5792999
Freephone: 008000 4636287 (008000 INFOCUS)

In Asia: InFocus ASA

238A Thomson Road • #18-01/04 Novena Square
Singapore 307684 • Phone: (65) 6334-9005 • Fax: (65) 6333-4525

InFocus and LP are registered trademarks and ProjectAbility is a trademark of InFocus Corporation. All other trademarks are used with permission or are for identification purposes only and are the property of their respective companies.
©2003 InFocus Corporation. All rights reserved. 825-0098-01. LP820_DS_E_V01.qxd 10/2003